



US009636990B2

(12) **United States Patent**
Kasuya et al.

(10) **Patent No.:** **US 9,636,990 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **HYBRID DRIVE APPARATUS**

(71) Applicant: **AISIN AW CO., LTD.**, Anjo-shi,
Aichi-ken (JP)

(72) Inventors: **Satoru Kasuya**, Nishio (JP); **Masashi Kito**, Anjo (JP); **Yuichi Seki**, Okazaki (JP); **Muneyuki Tsumura**, Anjo (JP)

(73) Assignee: **AISIN AW CO., LTD.**, Anjo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 316 days.

(21) Appl. No.: **14/422,930**

(22) PCT Filed: **Sep. 27, 2013**

(86) PCT No.: **PCT/JP2013/076412**

§ 371 (c)(1),

(2) Date: **Feb. 20, 2015**

(87) PCT Pub. No.: **WO2014/051110**

PCT Pub. Date: **Apr. 3, 2014**

(65) **Prior Publication Data**

US 2015/0239336 A1 Aug. 27, 2015

(30) **Foreign Application Priority Data**

Sep. 28, 2012 (JP) 2012-218395

(51) **Int. Cl.**

B60K 6/54 (2007.10)

B60K 6/405 (2007.10)

(Continued)

(52) **U.S. Cl.**

CPC **B60K 6/54** (2013.01); **B60K 6/387** (2013.01); **B60K 6/405** (2013.01); **B60K 6/48** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC .. Y02T 10/70; Y02T 10/7077; B60L 2240/36; F16D 2300/0214; F16D 25/0638; F16D

2300/26

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,830,164 A * 5/1989 Hays F16D 69/0408
188/250 G

5,123,387 A 6/1992 Jones

(Continued)

FOREIGN PATENT DOCUMENTS

JP H05-280370 A 10/1993

JP 2004-276913 A 10/2004

(Continued)

OTHER PUBLICATIONS

Nov. 19, 2013 Search Report issued in International Application No. PCT/JP2013/076412.

Primary Examiner — Victor MacArthur

(74) *Attorney, Agent, or Firm* — Oliff PLC

(57) **ABSTRACT**

A hybrid drive apparatus includes a rotary electric machine including a rotor capable of transmitting driving force to at least a speed change mechanism and a rotor hub that holds the rotor; a clutch; an oil hole that supplies oil from a radial inner side of the clutch toward the clutch; and a partition member disposed with a clearance provided in at least a portion in a circumferential direction between the rotor hub and the partition member on a radial inner side of the rotor hub.

10 Claims, 2 Drawing Sheets

